

Specification miniTOC



Customer Information	
Customer	
Contact Person	
Street	
Postal code /city	
Country	
Phone	
E-Mail	
<i>to be completed by membraPure GmbH</i>	
Project number	
Customer number	

Sample Parameters	
Range of Conductivity	μS/cm
Range of TOC	ppb
inlet pressure	bar
inlet temperature	°C
Monitoring of ring circuit	<input type="checkbox"/> no <input type="checkbox"/> yes

Specification miniTOC



Device Configuration		
Type	<input type="checkbox"/> Basic (= 1 Input)	<input type="checkbox"/> Professional / Pro (≤ 3 Inputs)
Protection Class IP 54	<input type="checkbox"/> no	<input type="checkbox"/> yes
Software CFR 21 part 11 conform	<input type="checkbox"/> no	<input type="checkbox"/> yes
Range of Conductivity	<input type="checkbox"/> $< 2 \mu\text{S/cm}$	<input type="checkbox"/> $< 10 \mu\text{S/cm}$ <input type="checkbox"/> $< 30 \mu\text{S/cm}$
Inlet pressure sensor	<input type="checkbox"/> no	<input type="checkbox"/> yes
Input trigger	<input type="checkbox"/> no	<input type="checkbox"/> yes
Interval mode (Pro only)	<input type="checkbox"/> no	<input type="checkbox"/> yes
Offline mode	<input type="checkbox"/> no	<input type="checkbox"/> yes
Autosampler (Pro only)	<input type="checkbox"/> no	<input type="checkbox"/> yes
Analogue Output	<input type="checkbox"/> No	<input type="checkbox"/> Yes
if yes		
Analogue output - 2 channels for conductivity, TOC and relay	<input type="checkbox"/> No	<input type="checkbox"/> Yes
Analogue output - 4 channels for conductivity, TOC (3 x) and relay (Pro only)	<input type="checkbox"/> No	<input type="checkbox"/> Yes

Specification miniTOC



Accessories	
<input type="checkbox"/>	Pressure reducer
<input type="checkbox"/>	Heat exchanger
<input type="checkbox"/>	Documents for IQ and OQ
<input type="checkbox"/>	Documents for PQ
<input type="checkbox"/>	Bottle and connector set for system suitability test (SST)
<input type="checkbox"/>	Stock solution for calibration
<input type="checkbox"/>	Stock solution for system suitability test (SST)
<input type="checkbox"/>	USP Traceable solutions for qualification (calibration and SST)

The device complied above corresponds to the concept of the customer and the possibilities of the company membraPure GmbH.

Date:	Signature Customer:	Signature membraPure GmbH: